

Technologies

**GLOBAL INTUITIVE COMMAND PANEL**

STANDARD mode : easy & intuitive

PRO mode : 100 % parameters

Technologies

**PUSH-PULL TORCH 24 V**

motor inside

**MB15**  
 Ø 0.8  
 160 A (100 %)  
 Original equipment :  
 Ø 0.6/0.8 - 1.0  
 4 m, 2.9 kg  
 044111

**MB25**  
 Ø 1.2  
 220 A (100 %)  
 Original equipment :  
 Ø 0.8 - 1.0/1.2  
 4 m, 3 kg  
 046283

More on p. 51

Option

**SPOOLGUN**  
 Ø 100 mm, 4 m  
 041486

Purge gas

Wire feed

**4 DRIVE ROLLERS**  
 Motor 75 W  
  
 Live electronic control

OR

OR

Synergies update

SD card  
 2 Gbits  
 050914



TESLA APPROVED

**PULSEMIG 300**

pack PULSEMIG 300 A1 022560	Type C Ø 0.8/1 (x2) original equipment	4 m, 35 mm <sup>2</sup> 043817	845 x 982 x 605 mm 033931	Cooling unit 5 L (liquid not included)	Cable support 032842	Fe / CrNi 250 A, 3 m, Air 040700	Alu —
pack PULSEMIG 300 A2 022584	Ø 0.8/1 (x2) original equipment	Alu Ø 1/1.2 042162 (x2)	845 x 982 x 605 mm 033931	—	Cable support 032842	—	250 A, 3 m, Air 040724
pack PULSEMIG 300 W1 022577	original equipment	4 m, 35 mm <sup>2</sup> 043817	—	WCT 1.3kW A 020344	Cable support 032842	300 A, 3 m, Liquid 040694	—
pack PULSEMIG 300 W2 022591	Ø 0.8/1 (x2) original equipment	Alu Ø 1/1.2 042162 (x2)	—	WCT 1.3kW A 020344	Cable support 032842	—	300 A, 3 m, Liquid 040748