

Multitorches double pulse

NEW RANGE

MIG/MAG welders

Latest generation colour screen 5" / 800 x 480 (WVGA)

Technologies

EASY MODE

10.0 mm Thickness
5.0 mm Wire
10A Current
1.0V Voltage
0 Arc Length

Pulse In Pulse - 2T
Ø 1.0 mm - AISi5Arg

EXPERT MODE

Pre-gas / Hot Start / Upslope / Downslope / Crater filler / Post-gas

10A Current
70% Duty
1.0 Hz
150% Pre-gas
50% Post-gas
0.0s Pre-gas

Pulse In Pulse - 2T
Ø 1.0 mm - AISi5Arg

ADVANCED MODE

Arc length adjustments

Soft Start

Pulse In Pulse - 2T
Ø 1.0 mm - AISi5Arg

UP TO 500 JOBS

can be saved

Job 01	Ø0.8 mm Alsi55Arg Standard 2T 3.5mm +B	06/07/2016 14:40
Job 02	Ø0.8 mm Alsi55Arg Standard 2T 5mm +B	06/07/2017 23:33
Job 08	Ø0.8 mm Alsi55Arg Manuel 2T 3.5mm +B	24/07/2017 14:58



SYNERGIES CARPULSE

Steel
CuSi3 / CuAl8
Alu

PROCESSES

Standard	Pulse
Double Pulse	Manual

Cold pulse

Technologies

PFC POWER FACTOR CORRECTION

185 V 265 V

(2.5 mm² max)
100 m

Technologies

PUSH-PULL TORCH 24 V

MB15 Ø 0.8 160 A (100%) Original equipment : Ø 0.6/0.8 - 1.0 4 m, 2.9 kg 044111	MB25 Ø 1.2 220 A (100%) Original equipment : Ø 0.8 - 1.0/1.2 4 m, 3 kg 046283	MB25 Ø 1.2 220 A (100%) Original equipment : Ø 0.8 - 1.0/1.2 6 m, 35 kg 048713
--	--	---

Option Ø 0.6/0.8 - 1.0
046290

SPOOLGUN

Motorized torch / Torche motorisée / Motorisiertes Brenner
Ø 100 mm
Ideal for :

- Steel / Acier / Stahl
- Stainless steel / Inox / Edelstahl
- Alu

 4 m
041486

5 pins Spoolgun connector 045699

CARPULSE 320-T3

	Fe / CrNi	Alu	Push-Pull	Contact tips box
pack CARPULSE 320-T3 036833	250 A, 3 m, Air 040700	250 A, 3 m, Air 040724	—	MB15/25 037458
pack CARPULSE 320-T3 PP 036840	250 A, 3 m, Air 040700	—	MB25, 4 m 046283	MB15/25 037458

NEW