


ATEX BALANCERS TECHNICAL FEATURES

	25	26	27	28	29	30	31	
kg	0,4÷3	1÷8	2÷14	2÷14	4÷25	20÷100	12÷70	Capacity
mm	1600	2000	2500	2500	2000	2100	2700	Stroke
●	●	●	●	●				Rugged construction, cast aluminium body
					●	●	●	Ribbed and sealed construction in aluminium alloy
●	●	●	●	●	●	●	●	Stainless steel rope
●	●	●	●	●				Adjustable capacity
					●	●	●	Adjustable capacity by means of a worm screw
●	●	●	●	●	●	●	●	Safety suspension
	●	●	●	●	●	●	●	Safety device against load dropping due to the spring breakage (capacity >3kg)
					●	●	●	Upper rotary suspension with safety hook
			●	●	●	●	●	Locking device to block the load at any height
●	●	●	●	●	●	●	●	Adjustable stroke limiting device
					●	●	●	Taper drum rotating on ball bearings
●	●	●	●	●	●	●	●	Cable guide in antifriction material
					●	●	●	Rotary upper hook with ball bearing
●	●	●	●	●	●	●	●	Inert spring drum assembly
●	●	●	●	●				Polyamides thimble
●	●	●	●	●	●	●	●	Operating temperature between + 5°C to + 60°C.

ON REQUEST OPTIONS F

					●			F: Brake device
--	--	--	--	--	---	--	--	-----------------