

# SUMMARY TABLE



TEKNEEL Workshop equipment	Power	SHUCKO 230 V 2P+N-TPE 50-60Hz	230 V	400 V	Battery	freq. kHz	AM	20°C	Cable length (m)	Handpiece length (m)	Cooling	Capacity (liters)	Weight (Kg)	Dimensions (YxZxX cm)
<b>DRAGON FLY</b> DF1 (DENT REMOVER)	0,4 kW	✓	/	/	/	20-60	2	20 minutes MAX POWER	3	3	Air Cooling	/	4	25x15x26
<b>DRAGON FLY-3</b> DF3 (4 ACCESSORIES)	3 kW	✓	/	/	/	20-60	20	20 minutes MAX POWER	3	3	Air Cooling	/	9	39x28x19
<b>BUTTERFLY</b> BFH01 <b>NEW!</b>	3,5 kW	✓	/	/	/	20-60	20	30 minutes MAX POWER	1,8	4	Liquid Cooling	1	7	21x45x26
<b>DRAGON 300</b> IHD03	3,7 kW	✓	/	/	/	20-60	20	45 minutes MAX POWER	3	6	Liquid Cooling	5	39	43x43x62
<b>EVOLUTION</b> IHDEVO <b>NEW!</b>	3,7 kW	✓	/	/	/	20-60	20	45 minutes (with cooling 20 min) MAX POWER	3	6	Liquid Cooling	5	39	43x43x62
<b>DRAGON 400</b> IHD04	3,7 kW	✓	/	/	/	20-60	20	continuous	3	10	BOOSTED Liquid Cooling	20	63	43x43x104
<b>PHOENIX</b> PHX05 <b>NEW!</b>	5 kW	/	/	/	✓	20-60	100	BATTERY LIFE 20 MINUTES	3	WITHOUT CABLE	Liquid Cooling	13	40	40x41x80
<b>DRAGON 500</b> IHD05	5,4 kW	/	16A	* 16A on request	/	20-50	25	continuous	3	10	Liquid Cooling	20	65	43x43x104
<b>DRAGON 700</b> IHD07	7,3 kW	/	32A	/	/	20-50	32	continuous	3	10	Liquid Cooling	20	65	43x43x104
<b>DRAGON 800</b> IHD08	8 kW	/	/	* 16A	/	15-50	16	continuous	4	10	Liquid Cooling	20	80	43x43x104
<b>DRAGON 1000</b> IHD1000	11 kW	/	/	* 16A	/	15-50	16	continuous	5	10	Liquid Cooling	20	96	50x50x100
<b>DRAGON 2000</b> IHD2000	16 kW	/	/	* 32A	/	15-50	25	continuous	6	10	Liquid Cooling	25	150	51x60x111
<b>EXPERIENCE</b> XP21	21 kW	/	/	* 32A	/	15-50	32	continuous	6	10	DOUBLE Liquid Cooling	30	190	101x64x95
<b>EXPERIENCE DUAL CORE</b> XP22 <b>NEW!</b>	22 kW	/	/	* 32A	/	10-50	32	continuous	6	10	DOUBLE Liquid Cooling	30	190	101x64x95
<b>TWIN POWER</b> 16+16 TWIN16	32 kW	/	/	* 63A	/	15-50	50	continuous	2 X 6	10	DOUBLE Liquid Cooling	25+25	250	101x64x95

TEKNEEL Workshop equipment	Power	SHUCKO 230 V 2P+N-TPE 50-60Hz	230 V	400 V	Battery	freq. kHz	AM	20°C	Cable length (m)	Handpiece length (m)	Cooling	Capacity (liters)	Weight (Kg)	Dimensions (YxZxX cm)	Plasma cutting up to 12mm 35% MAX 25A 35% @ 140°C	Welding TIG LIFT striking and MMA 35% @ 140°C
<b>CERBERUS 500</b> IHC500	5,4 kW	✓	16A	/	/	20-50	25	continuous	3	10	Liquid Cooling	20	65	43x43x104	✓	✓
<b>CERBERUS 700</b> IHC700 <b>NEW!</b>	7,3 kW	✓	32A	/	/	20-50	32	continuous	3	10	Liquid Cooling	20	65	43x43x104	✓	✓
<b>CERBERUS 800</b> IHC800 <b>NEW!</b>	8 kW	/	/	* 16A	/	15-50	16	continuous	4	10	Liquid Cooling	20	80	43x43x104	✓	✓
<b>CERBERUS 1000</b> IHC1000 <b>NEW!</b>	11 kW	/	/	* 16A	/	15-50	16	continuous	5	10	Liquid Cooling	20	96	50x50x100	✓	✓
<b>CERBERUS 2000</b> IHC2000 <b>NEW!</b>	16 kW	/	/	* 32A	/	15-50	25	continuous	6	10	Liquid Cooling	25	150	51x60x111	✓	✓

\* ON REQUEST DIFFERENT PLUGS